

STANDARD 12V - DRY LOAD

<text><text><text><text><text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text></text></text></text></text>	Parametrs		
Capadity Current19Ah 240ADimensionsMeigh175mm 155mmHeigh155mmHeigh604spCorrent Configuration CollegionCarto Configuration Acto Acto Acto Acto Mounting AngleMethodyCACA Acto Acto Acto Mounting AngleDeforemended Charging current Acto Mounting AngleMethodyCACA Acto Acto Acto Mounting AngleDeforemended Charging current BodyActo Acto<		12V	
Current240ADimensionsEngth175mmWidth100mmHeight155mmWeight6.04kgCase FeaturesEntrCal configurationLeft*Cal layout6.0TechnologyCACASecantoreded charging current1.9Mounting Angle36.0°Type of terminalCall ConfigurationImage: Side ViewImage: Side ViewFront ViewSide ViewImage: Side ViewSide ViewImage: Side View </td <td></td> <td></td> <td></td>			
Length Width:10mm 10mm 15mmMeight Withektrolyte6.04kgCase Features1Meight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Meight Meight Meight6.04kgMeight Meight Meight Meight Meight6.04kgMeight Meight Meight Meight6.04kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight <td< td=""><td>Current</td><td></td><td></td></td<>	Current		
Length Width:10mm 10mm 15mmMeight Withektrolyte6.04kgCase Features1Meight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Mithektrolyte6.04kgMeight Meight Meight Meight6.04kgMeight Meight Meight Meight Meight6.04kgMeight Meight Meight Meight6.04kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight100kgMeight Meight <td< td=""><td></td><td></td><td></td></td<>			
Length175mmWidth175mmWidth155mmWidth6.04kgCase FeaturesImage: Carca featuresCell configurationLeft+ 6TechnologyCarca featuresSeparatorCarca featuresMounting AngleCarca featuresType of terminalCarca featuresImage: Side ViewCarca featuresImage: Side ViewSide ViewImage: Side ViewCarca featuresImage: Side ViewSide ViewImage: Side ViewCarca featuresImage: Side ViewSide ViewImage: Side ViewCarca featuresImage: Side ViewCarca featuresImage: Side ViewCarca featuresImage: Side ViewSide ViewImage: Side V	Dimensions		make and first in a second second second
Width Height100mm 155mmWeight Wite leetrolyte6.04kgCarce FeaturesImage: Carce for the former state former state for the former s	Length	175mm	
Weight milectrolyte 6.04kg Case Features image: state of the sta		100mm	MILAN CO -COT
Weight Wite lectrolyte Case Features Cit configuration Left+ Case Features Prentogong CACA AGM AGM AGM AGM AGM Case AGM Bernended charging current 360' Arron View Side View Side View Case AGM Case A	Height	155mm	BOWER
Weight With electrolyte Case Features Cell configuration Left+ Call configuration			
With electrolyte 6,04kg Case Features Edit configuration Edit configuration Left+ Generation CA/CA Separator ACMA Separator ACMA Mounting Angle 360* Chrome View Side View Side View Tor View Tor View Side View Tor View Tor View Side View Tor V	Weight		
Subscription Left Calcanology CA/CA Sparator AGM Monting Angle CA/CA Some and the strength 19A Monting Angle 360° Strength Fort View side View of the strength Fort View Side View Side View of the strength Fort View Side View Si		6.041	12V/19Ah/220A(-18"C)
Case Features Cell configuration Left* Bernology Second configuration Main and the second configur	with electrolyte	6,04Kg	
Cell configuration Left+ Cell configuration CA/CA Separator CA/CA Recommended charging current 1.9A 360* 360* Cell Configuration Front View Side View Configuration Top View Side View Top View Top View Side View Top	Coop Eastures		
Cell configuration Left- Cell layout 6 Technology Technology CA/CA AGM Recommended charging current 1,9A 360° Type of terminal Cell Configuration Front View Side View 0 Top View	Case reatures		543
Cell layout 6 Technology Separator Recommended charging current 1.9A 360° Type of terminal Cell Configuration Front View Side View Top View	Cell configuration	Left+	120 TRANK/TUHR+2200XICCA) V)C2
Technology CACA Separator AGM Addition 1.9A 360° 360° Type of terminal Cell Configuration Front View Side View Top View		6	
Technology CACA Separator AGM Addition 1.9A 360° 360° Type of terminal Cell Configuration Front View Side View Top View			
Technology CACA Separator AGM Addition 1.9A 360° 360° Type of terminal Cell Configuration Front View Side View Top View	Technology		
Separator AGM Mounting Angle 19A 360° Type of terminal Cell Configuration Font View Side View Top View			
Recommended charging current 19A 360° Type of terminal Image: Configuration Cell Configuration Image: Configuration Image: Configuration			
Mounting Angle 360° Type of terminal Image: Configuration			
$ \begin{array}{c} \hline \\ \hline $			
Front View Side View O	Type of terminal		Cell Configuration
Front View Side View O	\bigcirc	 	
Top View			+
Top View	En al M		
	Front View S	side View	0
The date of issue of catalog card 04/201	Top View		
			The date of issue of catalog card 04/201

Batteries for all applications

www.bpower-battery.eu